



PATENT

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Application No. : 10/702,046 Confirmation No. : 7395
Applicant : Huaiyu PAN et al
Filed : November 6, 2003
TC/A.U. : 3744
Examiner : Unknown
Docket No. : 038871.52853US
Customer No. : 23911
Title : A PULSE TUBE REFRIGERATOR

CLAIM FOR PRIORITY UNDER 35 U.S.C. §119

Commissioner for Patents
P.O. Box 1450
Alexandria, VA 22313-1450

February 10, 2004

Sir:

The benefit of the filing date of prior foreign application No. 0226000.8, filed in Great Britain on November 7, 2002, is hereby requested and the right of priority under 35 U.S.C. §119 is hereby claimed.

In support of this claim, filed herewith is a certified copy of the original foreign application.

Respectfully submitted,

Gary R. Edwards
Registration No. 31,824

CROWELL & MORING, LLP
Intellectual Property Group
P.O. Box 14300
Washington, DC 20044-4300
Telephone No.: (202) 624-2500
Facsimile No.: (202) 628-8844
GRE:kms



INVESTOR IN PEOPLE


The Patent Office
Concept House
Cardiff Road
Newport
South Wales
NP10 8QQ

I, the undersigned, being an officer duly authorised in accordance with Section 74(1) and (4) of the Deregulation & Contracting Out Act 1994, to sign and issue certificates on behalf of the Comptroller-General, hereby certify that annexed hereto is a true copy of the documents as originally filed in connection with the patent application identified therein.

In accordance with the Patents (Companies Re-registration) Rules 1982, if a company named in this certificate and any accompanying documents has re-registered under the Companies Act 1980 with the same name as that with which it was registered immediately before re-registration save for the substitution as, or inclusion as, the last part of the name of the words "public limited company" or their equivalents in Welsh, references to the name of the company in this certificate and any accompanying documents shall be treated as references to the name with which it is so re-registered.

In accordance with the rules, the words "public limited company" may be replaced by p.l.c., plc, P.L.C. or PLC.

Re-registration under the Companies Act does not constitute a new legal entity but merely subjects the company to certain additional company law rules.



Signed



Dated 22 October 2003

Patents Form 1/77

Patents Act 1977
(Rule 16)The
Patent
Office07NOV02 E761833-1 D00393
P01/7700 0.00-0226000.8

Request for grant of a patent

(See the notes on the back of this form. You can also get an explanatory leaflet from the Patent Office to help you fill in this form)

THE PATENT OFFICE
- 7 NOV 2002
RECEIVED BY FAX

The Patent Office

Cardiff Road
Newport
Gwent NP10 8QQ

1. Your reference

2002P18297/GB /P72/EHE/K

E 7 NOV 2002

2. Patent application number
(The Patent Office will fill in this part)

0226000.8

3. Full name, address and postcode of the or of
each applicant (underline all surnames)OXFORD MAGNET TECHNOLOGY LTD.
WHARF ROAD, EYNSHAM
OXFORD OX8 1BP

Patents ADP number (if you know it)

647776002

If the applicant is a corporate body, give the
country/state of its incorporation

UNITED KINGDOM

4. Title of the invention

A Pulse Tube Refrigerator

5. Name of your agent (if you have one)

"Address for service" in the United Kingdom
to which all correspondence should be sent
(including the postcode)Siemens Shared Services
Intellectual Property Department
Siemens House, Oldbury
Bracknell, Berkshire, RG12 8FZ

Patents ADP number (if you know it)

7761000002

6. If you are declaring priority from one or more
earlier patent applications, give the country
and the date of filing of the or of each these
earlier applications and (if you know it) the or
each application numberCountry Priority application number
(if you know it)Date of filing
(day / month / year)7. If this application is divided or otherwise
derived from an earlier UK application,
give the number and the filing date of
the earlier application8. Is a statement of inventorship and of right
to grant of a patent required in support of
this request? (Answer 'Yes' if:
a) any application named in part 3 is not an inventor, or
b) there is an inventor who is not named as an
applicant, or
c) any named applicant is a corporate body.
See note (d))

Yes

Patents Form 1/77

Patents Form 1/77

Patents Act 1977
(Rule 16)The
Patent
Office

1/77

9. Enter the number of sheets for any of the following items you are filling with this form. Do not count copies of the same document

Continuation sheets of this form

Description	11
Claim(s)	3
Abstract	1
Drawing(s)	11




10. If you are also filing any of the following, state how many against each item.

Priority documents	-
Translation of priority documents	-
Statement of inventorship and right to grant a patent (Patents Form 7/77)	4
Request for preliminary examination and search (Patents Form 9/77)	1
Request for substantive examination (Patents Form 10/77)	-
Any other documents (please specify)	

11. We request the grant of a patent on the basis of this application

Signature

Date



Edward Humphrey-Evans

07.11.2002

12. Name and daytime telephone number of Person to contact in the United Kingdom

Edward Humphrey-Evans

+44 1344 39 6807

DUPLICATE

A PULSE TUBE REFRIGERATOR

Field of the invention

The present invention relates to pulse tube refrigerators for
5 recondensing cryogenic liquids. In particular, the present invention
relates to the same for magnetic resonance imaging systems.

Background to the Invention

In many cryogenic applications components, e.g.
10 superconducting coils for magnetic resonance imaging (MRI),
superconducting transformers, generators, electronics, are cooled by
keeping them in contact with a volume of liquefied gases (e.g. Helium,
Neon, Nitrogen, Argon, Methane). Any dissipation in the components
or heat getting into the system causes the volume to part boil off. To
15 account for the losses, replenishment is required. This service
operation is considered to be problematic by many users and great
efforts have been made over the years to introduce refrigerators that
recondense any lost liquid right back into the bath.

As an example of prior art, an embodiment of a two stage Gifford
20 McMahon (GM) coldhead recondenser of an MRI magnet is shown in
Figure 1. In order for the GM coldhead, indicated generally by 10, to
be removable for service or repair, it is inserted into a sock, which
connects the outside face of a vacuum vessel 16 (at room temperature)
to a helium bath 18 at 4K. MRI magnets are indicated at 20. The sock
25 is made of thin walled stainless steel tubes forming a first stage sleeve
12, and a second stage sleeve 14 in order to minimise heat conduction

- 2 -

from room temperature to the cold end of the sock operating at cryogenic temperatures. The sock is filled with helium gas 30, which is at about 4.2 K at the cold end and at room temperature at the warm end. The first stage sleeve 12 of the coldhead is connected to an intermediate heat station of the sock 22, in order to extract heat at an intermediate temperature, e.g. 40K-80 K, and to which sleeve 14 is also connected. The second stage of the coldhead 24 is connected to a helium gas recondenser 26. Heat arises from conduction of heat down through the neck, heat radiated from a thermal radiation shield 42 as well as any other sources of heat for example, from a mechanical suspension system for the magnet, (not shown) and from a service neck (also not shown) used for filling the bath with liquids, instrumentation wiring access, gas escape route etc. The intermediate section 22 shows a passage 38 to enable helium gas to flow from the volume encircled by sleeve 14. A number of passages may be annularly distributed about the intermediate section. The latter volume is also in fluid connection with the main bath 36 in which the magnet 20 is placed. Also shown is a flange 40 associated with sleeve 12 to assist in attaching the sock to the vacuum vessel 16. A radiation shield 42 is placed intermediate the helium bath and the wall of the outer vacuum vessel.

The second stage of the coldhead is acting as a recondensor at about 4.2 K. As it is slightly colder than the surrounding He gas, gas is condensed on the surface (which can be equipped with fins to increase surface area) and is dripped back into the liquid reservoir. Condensation locally reduces pressure, which pulls more gas towards the second stage. It has been calculated that there are hardly any losses due to

- 3 -

natural convection of Helium, which has been verified experimentally provided that the coldhead and the sock are vertically oriented (defined as the warm end pointing upwards). Any small differences in the temperature profiles of the Gifford McMahon cooler and the walls
5 would set up gravity assisted gas convection, as the density change of gas with temperature is great (e.g. at 4.2. K the density is 16 kg/m^3 ; at 300 K the density is 0.16 kg/m^3). Convection tends to equilibrate the temperature profiles of the sock wall and the refrigerator. The residual heat losses are small.

10 When the arrangement is tilted, natural convection sets up huge losses. A solution to this problem has been described in US Patent, US-A-5,583,472, to Mitsubishi. Nevertheless, this will not be further discussed here, as this document relates to arrangements which are vertically oriented or at small angles ($< 30^\circ$) to the vertical.

15 It has been shown that Pulse Tube Refrigerators (PTRs) can achieve useful cooling at temperatures of 4.2 K (the boiling point of liquid helium at normal pressure) and below (C. Wang and P.E. Gifford, Advances in Cryogenic Engineering, 45, Edited by Shu et al., Kluwer Academic/Plenum Publishers, 2000, pp. 1-7). Pulse tube refrigerators
20 are attractive, because they avoid any moving parts in the cold part of the refrigerator, thus reducing vibrations and wear of the refrigerator. Referring now to Figure 2, there is shown a PTR 50 comprising an arrangement of separate tubes, which are joined together at heat stations. There is one regenerator tube 52, 54 per stage, which is filled
25 with solid materials in different forms (e.g. meshes, packed spheres, powders). The materials act as a heat buffer and exchange heat with

- 4 -

the working fluid of the PTR (usually He gas at a pressure of 1.5-2.5 MPa). There is one pulse tube 56, 58 per stage, which is hollow and used for expansion and compression of the working fluid. In two stage PTRs, the second stage pulse tube 56 usually links the second stage 60 with the warm end 62 at room temperature, the first stage pulse tube 58 linking the first stage 64 with the warm end.

It has been found, that PTRs operating in vacuum under optimum conditions usually develop temperature profiles along the length of the tubes that are significantly different one tube to another in the same temperature range and also from what would be a steady state temperature profile in a sock. This is shown in Figure 3.

Another prior art pulse tube refrigerator arrangement is shown in Figure 4 wherein a pulse tube is inserted into a sock, and is exposed to a helium atmosphere wherein gravity induced convection currents 70, 72 are set up in the first and second stages. The PTR unit 50 is provided with cold stages 31, 33 which are set in a recess in an outer vacuum container 16. A radiation shield 42 is provided which is in thermal contact with first sleeve end 22. A recondenser 26 is shown on the end wall of second stage 33. If at a given height the temperatures of the different components are not equal, the warmer components will heat the surrounding helium, giving it buoyancy to rise, while at the colder components the gas is cooled and drops down. The resulting thermal losses are huge, as the density difference of helium gas at 1 bar changes by a factor of about 100 between 4.2 K and 300 K. The net cooling power of a PTR might be e.g. 40 W at 50 K, and 0.5 W to 1 W at 4.2 K. The losses have been calculated to be of the order of 5-20 W.

- 5 -

The internal working process of a pulse tube will, in general, be affected although this is not encountered in GM refrigerators. In a PTR, the optimum temperature profile in the tubes, which is a basis for optimum performance, arises through a delicate process balancing the influences of many parameters, e.g. geometries of all tubes, flow resistivities, velocities, heat transfer coefficients, valve settings etc. (A description can be found in Ray Radebaugh, proceedings of the 6th International Cryogenic Engineering Conference, Kitakyushu, Japan, 20-24 May, 1996, pp. 22-44).

Therefore, in a helium environment, PTRs do not necessarily reach temperatures of 4 K, although they are capable of doing so in vacuum. Nevertheless, if the PTR is inserted in a vacuum sock with a heat contact to 4 K through a solid wall, it would work normally. Such a solution has been described for a GM refrigerator (US Patent US-A-5,613,367 to William E. Chen, GE) although the use of a PTR would be possible and be straightforward. The disadvantage, however, is that the thermal contact of the coldhead at 4 K would produce a thermal impedance, which effectively reduces the available power for refrigeration. As an example, with a state of the art thermal joint made from an Indium washer, a thermal contact resistance of 0.5 K/W can be achieved at 4 K (see e.g. US-A-5,918,470 to GE). If a cryocooler can absorb 1 W at 4.2 K (e.g. the model RDK 408 by Sumitomo Heavy Industries) then the temperature of the recondensor would rise to 4.7 K, which would reduce the current carrying capability of the superconducting wire drastically. Alternatively, a stronger cryocooler

- 6 -

would be required to produce 1 W at 3.7 K initially to make the cooling power available on the far side of the joint.

Figure 5 shows an example of such a PTR arrangement 76. The component features are substantially the same as shown in Figure 4. Thermal washer 78 is provided between the second stage of the PTR coldhead and a finned heat sink 26. A helium-tight wall is provided between the thermal washer and the heat sink.

Object of the invention

The present invention seeks to provide an improved pulse tube refrigerator.

Statement of the Invention

In accordance with a first aspect of the invention, there is provided a pulse tube refrigerator PTR arrangement within a cryogenic apparatus, wherein a regenerator tube of a PTR is finned. Ideally, there is a plurality of fins. The fins conveniently comprise annular discs and are spaced apart along the length of the regenerator tube. Alternatively the fins comprise outwardly directed fingers or prongs. The fins may also comprise a single spiral arrangement. Conveniently, an associated sock surrounds all the tubes of the pulse tube, leaving only a small annular gap between the regenerator and pulse tubes and a wall of the sock. The walls of the tubes can be fabricated from materials such as thin gauge stainless steel or alloys

The invention provides a regenerator for a PTR which can act as a distributed cooler, that is to say that there is refrigeration power along

- 7 -

the length of the regenerator. This means that the regenerator can intercept (absorb) some of the heat being conducted down the refrigerator sock (neck tube, helium column plus other elements). Whilst the absorption of this heat degrades the performance of the second stage, in one sense, this degradation is less than the heat which is extracted (intercepted) by the regenerator and therefore there is a net gain in cooling power. By placing fins along the regenerator the distributed cooling power of the regenerator is increased by enhancing the heat transfer (by increasing the surface area available for the transfer) to the helium column (and therefore the neck tube etc) that is to say, the fins or baffles, are believed to increase the surface area available for distributed heat transfer from the helium atmosphere to the regenerator.

15 Brief description of the figures

The invention may be understood more readily, and various other aspects and features of the invention may become apparent from consideration of the following description and the figures as shown in the accompanying drawing sheets, wherein:

20 Figure 1 shows a two stage Gifford McMahon coldhead recondenser in a MRI magnet;

Figure 2 shows a PTR consisting of an arrangement of separate tubes, which are joined together at the heat stations;

Figure 3 shows a temperature profile in a sock;

25 Figure 4 shows a pulse tube inserted into a sock;

- 8 -

Figure 5 shows a prior art example of a pulse tube with a removable thermal contact;

Figure 6 shows a first embodiment of the invention;

Figure 6A shows a cross-section of a regenerator tube of the first
5 embodiment;

Figures 7A-G shows various forms of regenerator tubes; and

Figures 8-10 show further variations of the invention.

Detailed description of the invention

10 There will now be described, by way of example, the best mode contemplated by the inventors for carrying out the invention. In the following description, numerous specific details are set out in order to provide a complete understanding of the present invention. It will be apparent, however, to those skilled in the art, that the present invention
15 may be put into practice with variations from the specific embodiments.

Referring now to Figure 6, there is shown a first embodiment of the invention, wherein a 2-stage PTR arrangement 90 is shown. Regenerator tubes 92, 94 and pulse tubes 96, 98 are shown with regenerator tube 94 being finned.

20 Figure 6A shows a cross-section through the regenerator tube 94 showing annular fin 104 surrounding tube 94 in the form of an annular disc. Conveniently the tube wall and the fins are manufactured simultaneously, preferably from the same material which is moderately thermally conductive, such as an austenitic stainless steel. Other
25 materials that could be used include brass and aluminium alloys. However, if the component materials of the fins and tube are different,

- 9 -

then it is preferable that the fins are made of a material that is highly thermally conductive and that the tube is made of a material that is moderately thermally conductive. For low pressure PTRs, it would be possible to employ a composite material, which materials can be moderately thermally conductive, and provide fins made from copper or some other highly thermally conductive material, which would be bonded to the composite. It is to be noted that pure metals can be highly thermally conductive at low temperatures.

The fins should have very good thermal contact with the regenerator which can be achieved by, for example, soldering, welding or brazing. The fins intercept the heat being transferred down the helium columns, neck tube and other elements within the neck. It is believed that the absorption of the heat may degrade the performance of the second stage, although it is believed that this degradation in power is less than the heat extracted by the regenerator and therefore there is a net gain in the available cooling power and thus the recondensation rate of helium gas. The provision of fins increase the distributed cooling due to the enhanced heat transfer with the gas column arising as a result of the increased surface area available. These fins can also be used on the first stage regenerator in order to minimise the heat load from the 300k stage to the first stage. Another advantage for this configuration is that these fins can work as barriers against the natural convection between the high temperature and low temperature levels. Accordingly, the natural convection and its heat load to the second stage may be reduced.

- 10 -

In Figures 7A-F, different mechanical forms of the finned tube 94 are shown. In Figure 7A the finning comprises an array of annular discs 120 about a straight tube. The tube wall is thick enough to withstand the surrounding helium pressure during evacuation without any buckling. The fins are conveniently placed at equi-spaced intervals and are preferably of the same dimension.

In figure 7B, the fin comprises a spiral tape 122, affixed to the regenerator tube 94". In Figure 7C the fins comprise spikes 126 about tube 94"', in an arrangement somewhat akin to the spikes of a hedgehog. This arrangement would not, however, reduce convection currents about the tube, although would allow easier gas flow past the tube if it was required, for example, during a quench.

In figure 7D the tube 128 is corrugated in an arrangement similar to accordion bellows. In figure 7E plates 130 are placed about tube 94''', the plates being attached such that they are parallel with the axis of the tube. Tube 132 is corrugated with the axis of corrugation being parallel with the axis of the tube.

The tube of Figure 7F is corrugated with creases arranged parallel with the axis of the tube. In figure 7G the fins comprise annular rings which cover only a portion of the length of the tube. This sort of tube is preferable for the upper sections since, as can be seen with reference to Figure 3, that the temperature of the neck tube and the first regenerator correspond. That is to say to have a first regeneration tube fully finned along its length would be counter-productive to efficient operation.

- 11 -

The fins for individual tubes can differ amongst each other. In some applications it may be necessary to provide fins on the first stage and the second stage regenerators. The teaching of the present invention can be applied with the teaching disclosed in the PCT patent application number PCT/EP02/11882. In other words, in addition to the regeneration tubes having fins to aid heat conduction through the tube walls, the pulse tubes may be insulated to reduce heat conduction through the tube walls.

Figure 8 shows pulse tubes 101, 103 with insulating sleeves and regeneration tube 94 with fins 104. Figure 9 shows only pulse tube 101 with an insulating sleeve and regeneration tube 94 with fins. Figure 10 shows a similar arrangement to figure 8 except that regeneration tube 92 is also provided with fin 102.

While most applications cryogenic temperatures, e.g. at or around 4 K for MRI apparatus operate with two stage coolers, the same technology can also be applied to single stage coolers or three and more stage coolers.

- 12 -

CLAIMS

1. A pulse tube refrigerator (PTR) arrangement within a cryogenic apparatus, wherein a regenerator tube of the PTR is finned.
5
2. A PTR arrangement according to claim 1, wherein a first regenerator tube is finned across part of the length of the tube.
3. A PTR arrangement according to claim 1 or 2, wherein the PTR
10 arrangement comprises two stages and the second stage regenerator tube is finned.
4. A PTR arrangement according to claim 1 or 2, wherein the PTR arrangement is a multi-stage PTR arrangement.
15
5. A PTR arrangement according to any one of claims 1 to 4, wherein the regenerator tube is fabricated from a thin walled alloy which has a moderate thermal conductivity at low temperatures.
- 20 6. A PTR arrangement according to any one of claims 1 to 5, wherein the fins comprise annular rings.
7. A PTR arrangement according to claim 6, wherein the annular rings are spaced apart regularly, along an outside of the regenerator
25 tube.

- 13 -

8. A PTR arrangement according to claim 6, wherein the annular rings are not of a uniform size.

9. A PTR arrangement according to any one of claims 1 to 5,
5 wherein the fins comprise one or more spirally arranged strip sheets.

10. A PTR arrangement according to any one of claims 1 to 5,
wherein the fins comprise outwardly extending prongs.

10 11. A PTR arrangement according to any one of claims 1 to 5,
wherein the fins comprise rectangular sheets attached about the
circumference of the regenerator tube.

12. A PTR arrangement according to any one of claims 1 to 5,
15 wherein the fins comprise the wall of the tube which is corrugated either
axially with respect to an axis of the tube or perpendicularly with
respect to said axis.

13. A PTR arrangement according to any one of claims 1 to 5,
20 wherein the fins comprise one or more types of fin according to claims
6 to 12.

14. A PTR arrangement according to any one of claims 1 to 13,
wherein one or more pulse tubes have insulated walls.

25

- 14 -

15. A pulse tube refrigerator PTR according to any one of claims 1-12, wherein the PTR is associated with a magnetic resonance imaging apparatus.

5 16. A method of using a pulse tube refrigerator (PTR) arrangement within a cryogenic apparatus wherein the regenerator tube of the PTR arrangement is thinned, the method comprising the step of transferring heat from an atmosphere surrounding the tubes of the PTR assembly to the regenerator tube via fins associated with the regenerator tube.

10

17. A method according to claim 16 wherein the recondensor is associated with a magnetic resonance imaging apparatus.


- 15 -

ABSTRACT
A PULSE TUBE REFRIGERATOR

The present invention relates to pulse tube refrigerators for
5 recondensing cryogenic liquids. In particular, the present invention
relates to the same for magnetic resonance imaging systems. In many
cryogenic applications components, e.g. superconducting coils for
magnetic resonance imaging (mri), superconducting transformers,
generators, electronics, are cooled by keeping them in contact with a
10 volume of liquified gases (e.g. helium, neon, nitrogen, argon, methane).
In a first aspect, the present invention provides a pulse tube refrigerator
PTR pulse tube refrigerator (PTR) arrangement within a cryogenic
apparatus, wherein a regenerator tube of the PTR is finned. In this
configuration the fins or baffles, are believed to increase the surface
15 area available for distributed heat transfer from the helium atmosphere
to the regenerator.

1/11

Figure 1



2/11




Figure 2

3/11





Figure 3

4/11

Figure 4



5/11




Figure 5

6/11

Figure 6




Figure 6A

7/11

Figure 7a




Figure 7b




Figure 7c




Figure 7d





Figure
7e



8/11

Figure
7f





Figure
7g



9/11




FIGURE 8

10/11




FIGURE 9

11/11





FIGURE 10



A PULSE TUBE REFRIGERATOR

Field of the invention

The present invention relates to pulse tube refrigerators for
5 recondensing cryogenic liquids. In particular, the present invention
relates to the same for magnetic resonance imaging systems.

Background to the Invention

In many cryogenic applications components, e.g. superconducting
10 coils for magnetic resonance imaging (MRI), superconducting
transformers, generators, electronics, are cooled by keeping them in
contact with a volume of liquefied gases (e.g. Helium, Neon, Nitrogen,
Argon, Methane). Any dissipation in the components or heat getting into
the system causes the volume to part boil off. To account for the losses,
15 replenishment is required. This service operation is considered to be
problematic by many users and great efforts have been made over the
years to introduce refrigerators that recondense any lost liquid right back
into the bath.

As an example of prior art, an embodiment of a two stage Gifford
20 McMahon (GM) coldhead recondenser of an MRI magnet is shown in
Figure 1. In order for the GM coldhead, indicated generally by 10, to be
removable for service or repair, it is inserted into a sock, which connects
the outside face of a vacuum vessel 16 (at room temperature) to a helium
bath 18 at 4K. MRI magnets are indicated at 20. The sock is made of thin
25 walled stainless steel tubes forming a first stage sleeve 12, and a second
stage sleeve 14 in order to minimise heat conduction from room

temperature to the cold end of the sock operating at cryogenic temperatures. The sock is filled with helium gas 30, which is at about 4.2 K at the cold end and at room temperature at the warm end. The first stage sleeve 12 of the coldhead is connected to an intermediate heat station of the sock 22, in order to extract heat at an intermediate temperature, e.g. 40K-80 K, and to which sleeve 14 is also connected. The second stage of the coldhead 24 is connected to a helium gas recondenser 26. Heat arises from conduction of heat down through the neck, heat radiated from a thermal radiation shield 42 as well as any other sources of heat for example, from a mechanical suspension system for the magnet, (not shown) and from a service neck (also not shown) used for filling the bath with liquids, instrumentation wiring access, gas escape route etc. The intermediate section 22 shows a passage 38 to enable helium gas to flow from the volume encircled by sleeve 14. A number of passages may be annularly distributed about the intermediate section. The latter volume is also in fluid connection with the main bath 36 in which the magnet 20 is placed. Also shown is a flange 40 associated with sleeve 12 to assist in attaching the sock to the vacuum vessel 16. A radiation shield 42 is placed intermediate the helium bath and the wall of the outer vacuum vessel.

The second stage of the coldhead is acting as a recondensor at about 4.2 K. As it is slightly colder than the surrounding He gas, gas is condensed on the surface (which can be equipped with fins to increase surface area) and is dripped back into the liquid reservoir. Condensation locally reduces pressure, which pulls more gas towards the second stage. It has been calculated that there are hardly any losses due to natural

convection of Helium, which has been verified experimentally provided that the coldhead and the sock are vertically oriented (defined as the warm end pointing upwards). Any small differences in the temperature profiles of the Gifford McMahon cooler and the walls would set up gravity assisted gas convection, as the density change of gas with temperature is great (e.g. at 4.2 K the density is 16 kg/m^3 ; at 300 K the density is 0.16 kg/m^3). Convection tends to equilibrate the temperature profiles of the sock wall and the refrigerator. The residual heat losses are small.

10 When the arrangement is tilted, natural convection sets up huge losses. A solution to this problem has been described in US Patent, US-A-5,583,472, to Mitsubishi. Nevertheless, this will not be further discussed here, as this document relates to arrangements which are vertically oriented or at small angles ($< 30^\circ$) to the vertical.

15 It has been shown that Pulse Tube Refrigerators (PTRs) can achieve useful cooling at temperatures of 4.2 K (the boiling point of liquid helium at normal pressure) and below (C. Wang and P.E. Gifford, Advances in Cryogenic Engineering, 45, Edited by Shu et al., Kluwer Academic/Plenum Publishers, 2000, pp. 1-7). Pulse tube refrigerators are attractive, because they avoid any moving parts in the cold part of the refrigerator, thus reducing vibrations and wear of the refrigerator. Referring now to Figure 2, there is shown a PTR 50 comprising an arrangement of separate tubes, which are joined together at heat stations. There is one regenerator tube 52, 54 per stage, which is filled with solid materials in different forms (e.g. meshes, packed spheres, powders). The materials act as a heat buffer and exchange heat with the working fluid of

20
25

the PTR (usually He gas at a pressure of 1.5-2.5 MPa). There is one pulse tube 56, 58 per stage, which is hollow and used for expansion and compression of the working fluid. In two stage PTRs, the second stage pulse tube 56 usually links the second stage 60 with the warm end 62 at room temperature, the first stage pulse tube 58 linking the first stage 64 with the warm end.

It has been found, that PTRs operating in vacuum under optimum conditions usually develop temperature profiles along the length of the tubes that are significantly different one tube to another in the same temperature range and also from what would be a steady state temperature profile in a sock. This is shown in Figure 3.

Another prior art pulse tube refrigerator arrangement is shown in Figure 4 wherein a pulse tube is inserted into a sock, and is exposed to a helium atmosphere wherein gravity induced convection currents 70, 72 are set up in the first and second stages. The PTR unit 50 is provided with cold stages 31, 33 which are set in a recess in an outer vacuum container 16. A radiation shield 42 is provided which is in thermal contact with first sleeve end 22. A recondenser 26 is shown on the end wall of second stage 33. If at a given height the temperatures of the different components are not equal, the warmer components will heat the surrounding helium, giving it buoyancy to rise, while at the colder components the gas is cooled and drops down. The resulting thermal losses are huge, as the density difference of helium gas at 1 bar changes by a factor of about 100 between 4.2 K and 300 K. The net cooling power of a PTR might be e.g. 40 W at 50 K, and 0.5 W to 1 W at 4.2 K. The losses have been calculated to be of the order of 5-20 W. The

internal working process of a pulse tube will, in general, be affected although this is not encountered in GM refrigerators. In a PTR, the optimum temperature profile in the tubes, which is a basis for optimum performance, arises through a delicate process balancing the influences of
5 many parameters, e.g. geometries of all tubes, flow resistivities, velocities, heat transfer coefficients, valve settings etc. (A description can be found in Ray Radebaugh, proceedings of the 6th International Cryogenic Engineering Conference, Kitakyushu, Japan, 20-24 May, 1996, pp. 22-44).

10 Therefore, in a helium environment, PTRs do not necessarily reach temperatures of 4 K, although they are capable of doing so in vacuum. Nevertheless, if the PTR is inserted in a vacuum sock with a heat contact to 4 K through a solid wall, it would work normally. Such a solution has been described for a GM refrigerator (US Patent US-A-5,613,367 to
15 William E. Chen, GE) although the use of a PTR would be possible and be straightforward. The disadvantage, however, is that the thermal contact of the coldhead at 4 K would produce a thermal impedance, which effectively reduces the available power for refrigeration. As an example, with a state of the art thermal joint made from an Indium
20 washer, a thermal contact resistance of 0.5 K/W can be achieved at 4 K (see e.g. US-A-5,918,470 to GE). If a cryocooler can absorb 1 W at 4.2 K (e.g. the model RDK 408 by Sumitomo Heavy Industries) then the temperature of the recondensor would rise to 4.7 K, which would reduce the current carrying capability of the superconducting wire drastically.
25 Alternatively, a stronger cryocooler would be required to produce 1 W at

3.7 K initially to make the cooling power available on the far side of the joint.

Figure 5 shows an example of such a PTR arrangement 76. The component features are substantially the same as shown in Figure 4.

5 Thermal washer 78 is provided between the second stage of the PTR coldhead and a finned heat sink 26. A helium-tight wall is provided between the thermal washer and the heat sink.

Object of the invention

10 The present invention seeks to provide an improved pulse tube refrigerator.

Statement of the Invention

In accordance with a first aspect of the invention, there is provided

15 a pulse tube refrigerator PTR arrangement within a cryogenic apparatus, wherein a regenerator tube of a PTR is finned. Ideally, there is a plurality of fins. The fins conveniently comprise annular discs and are spaced apart along the length of the regenerator tube. Alternatively the fins comprise outwardly directed fingers or prongs. The fins may also

20 comprise a single spiral arrangement. Conveniently, an associated sock surrounds all the tubes of the pulse tube, leaving only a small annular gap between the regenerator and pulse tubes and a wall of the sock. The walls of the tubes can be fabricated from materials such as thin gauge stainless steel or alloys

25 The invention provides a regenerator for a PTR which can act as a distributed cooler, that is to say that there is refrigeration power along the

length of the regenerator. This means that the regenerator can intercept (absorb) some of the heat being conducted down the refrigerator sock (neck tube, helium column plus other elements). Whilst the absorption of this heat degrades the performance of the second stage, in one sense, this degradation is less than the heat which is extracted (intercepted) by the regenerator and therefore there is a net gain in cooling power. By placing fins along the regenerator the distributed cooling power of the regenerator is increased by enhancing the heat transfer (by increasing the surface area available for the transfer) to the helium column (and therefore the neck tube etc) that is to say, the fins or baffles, are believed to increase the surface area available for distributed heat transfer from the helium atmosphere to the regenerator.

Brief description of the figures

The invention may be understood more readily, and various other aspects and features of the invention may become apparent from consideration of the following description and the figures as shown in the accompanying drawing sheets, wherein:

Figure 1 shows a two stage Gifford McMahon coldhead recondenser in a MRI magnet;

Figure 2 shows a PTR consisting of an arrangement of separate tubes, which are joined together at the heat stations;

Figure 3 shows a temperature profile in a sock;

Figure 4 shows a pulse tube inserted into a sock;

Figure 5 shows a prior art example of a pulse tube with a removable thermal contact;

Figure 6 shows a first embodiment of the invention;

Figure 6A shows a cross-section of a regenerator tube of the first embodiment;

Figures 7A-G shows various forms of regenerator tubes; and

5 Figures 8-10 show further variations of the invention.

Detailed description of the invention

There will now be described, by way of example, the best mode contemplated by the inventors for carrying out the invention. In the following description, numerous specific details are set out in order to provide a complete understanding of the present invention. It will be apparent, however, to those skilled in the art, that the present invention may be put into practice with variations from the specific embodiments.

Referring now to Figure 6, there is shown a first embodiment of the invention, wherein a 2-stage PTR arrangement 90 is shown. Regenerator tubes 92, 94 and pulse tubes 96, 98 are shown with regenerator tube 94 being finned.

Figure 6A shows a cross-section through the regenerator tube 94 showing annular fin 104 surrounding tube 94 in the form of an annular disc. Conveniently the tube wall and the fins are manufactured simultaneously, preferably from the same material which is moderately thermally conductive, such as an austenitic stainless steel. Other materials that could be used include brass and aluminium alloys. However, if the component materials of the fins and tube are different, then it is preferable that the fins are made of a material that is highly thermally conductive and that the tube is made of a material that is

moderately thermally conductive. For low pressure PTRs, it would be possible to employ a composite material, which materials can be moderately thermally conductive, and provide fins made from copper or some other highly thermally conductive material, which would be bonded
5 to the composite. It is to be noted that pure metals can be highly thermally conductive at low temperatures.

The fins should have very good thermal contact with the regenerator which can be achieved by, for example, soldering, welding or brazing. The fins intercept the heat being transferred down the helium
10 columns, neck tube and other elements within the neck. It is believed that the absorption of the heat may degrade the performance of the second stage, although it is believed that this degradation in power is less than the heat extracted by the regenerator and therefore there is a net gain in the available cooling power and thus the recondensation rate of helium gas.
15 The provision of fins increase the distributed cooling due to the enhanced heat transfer with the gas column arising as a result of the increased surface area available. These fins can also be used on the first stage regenerator in order to minimise the heat load from the 300k stage to the first stage. Another advantage for this configuration is that these fins can
20 work as barriers against the natural convection between the high temperature and low temperature levels. Accordingly, the natural convection and its heat load to the second stage may be reduced.

In Figures 7A-F, different mechanical forms of the finned tube 94 are shown. In Figure 7A the finning comprises an array of annular discs
25 120 about a straight tube. The tube wall is thick enough to withstand the surrounding helium pressure during evacuation without any buckling. The

fins are conveniently placed at equi-spaced intervals and are preferably of the same dimension.

In figure 7B, the fin comprises a spiral tape 122, affixed to the regenerator tube 94". In Figure 7C the fins comprise spikes 126 about
5 tube 94"', in an arrangement somewhat akin to the spikes of a hedgehog. This arrangement would not, however, reduce convection currents about the tube, although would allow easier gas flow past the tube if it was required, for example, during a quench.

In figure 7D the tube 128 is corrugated in an arrangement similar to
10 accordion bellows. In figure 7E plates 130 are placed about tube 94'''; the plates being attached such that they are parallel with the axis of the tube. Tube 132 is corrugated with the axis of corrugation being parallel with the axis of the tube.

The tube of Figure 7F is corrugated with creases arranged parallel
15 with the axis of the tube. In figure 7G the fins comprise annular fins which cover only a portion of the length of the tube. This sort of tube is preferable for the upper sections since, as can be seen with reference to Figure 3, that the temperature of the neck tube and the first regenerator correspond. That is to say to have a first regeneration tube fully finned
20 along its length would be counter-productive to efficient operation.

The fins for individual tubes can differ amongst each other. In some applications it may be necessary to provide fins on the first stage and the second stage regenerators. The teaching of the present invention can be applied with the teaching disclosed in the PCT patent application
25 number PCT/EP02/11882. In other words, in addition to the regeneration

tubes having fins to aid heat conduction through the tube walls, the pulse tubes may be insulated to reduce heat conduction through the tube walls.

Figure 8 shows pulse tubes 101, 103 with insulating sleeves and regeneration tube 94 with fins 104. Figure 9 shows only pulse tube 101
5 with an insulating sleeve and regeneration tube 94 with fins. Figure 10 shows a similar arrangement to figure 8 except that regeneration tube 92 is also provided with fin 102.

While most applications cryogenic temperatures, e.g. at or around 4 K for MRI apparatus operate with two stage coolers, the same technology
10 can also be applied to single stage coolers or three and more stage coolers.

CLAIMS

1. A pulse tube refrigerator (PTR) arrangement within a cryogenic apparatus, wherein a regenerator tube of the PTR is finned.
- 5 2. A PTR arrangement according to claim 1, wherein a first regenerator tube is finned across part of the length of the tube.
3. A PTR arrangement according to claim 1, wherein the PTR
10 arrangement comprises two stages and the second stage regenerator tube is finned.
4. A PTR arrangement according to claim 1, wherein the PTR arrangement is a multi-stage PTR arrangement.
- 15 5. A PTR arrangement according to claim 1, wherein the regenerator tube is fabricated from a thin walled alloy which has a moderate thermal conductivity at low temperatures.
- 20 6. A PTR arrangement according to claim 1, wherein the fins comprise annular fins.
7. A PTR arrangement according to claim 6, wherein the annular fins are spaced apart regularly, along an outside of the regenerator tube.

25

8. A PTR arrangement according to claim 6, wherein the annular fins are not of a uniform size.
9. A PTR arrangement according to claim 1, wherein the fins
5 comprise one or more spirally arranged strip sheets.
10. A PTR arrangement according to claim 1, wherein the fins comprise outwardly extending prongs.
- 10 11. A PTR arrangement according to claim 1, wherein the fins comprise rectangular sheets attached about the circumference of the regenerator tube, the sheets being attached along one edge to the regenerator tube.
- 15 12. A PTR arrangement according to claim 1, wherein the regenerator tube is corrugated whereby to define fins which comprise part of the wall of the tube, which is corrugated either axially with respect to an axis of the tube or perpendicularly with respect to said axis.
- 20 13. A PTR arrangement according to claim 1, wherein the fins comprise one or more types of fin..
14. A PTR arrangement according to claim 1, wherein one or more pulse tubes have insulated walls.

15. A pulse tube refrigerator PTR according to claim 1, wherein the PTR is associated with a magnetic resonance imaging apparatus.

16. A method of using a pulse tube refrigerator (PTR) arrangement
5 within a cryogenic apparatus wherein the regenerator tube of the PTR arrangement is finned, the method comprising the step of transferring heat from an atmosphere surrounding the tubes of the PTR assembly to the regenerator tube via fins associated with the regenerator tube.

10 17. A method according to claim 16 wherein the recondensor is associated with a magnetic resonance imaging apparatus.

ABSTRACT
A PULSE TUBE REFRIGERATOR

The present invention relates to pulse tube refrigerators for
5 recondensing cryogenic liquids. In particular, the present invention
relates to the same for magnetic resonance imaging systems. In many
cryogenic applications components, e.g. superconducting coils for
magnetic resonance imaging (mri), superconducting transformers,
generators, electronics, are cooled by keeping them in contact with a
10 volume of liquified gases (e.g. helium, neon, nitrogen, argon, methane). In
a first aspect, the present invention provides a pulse tube refrigerator PTR
pulse tube refrigerator (PTR) arrangement within a cryogenic apparatus,
wherein a regenerator tube of the PTR is finned. In this configuration the
fins or baffles, are believed to increase the surface area available for
15 distributed heat transfer from the helium atmosphere to the regenerator.

Figure 1




Figure 2




Figure 3





Figure 4






Figure 5

Figure 6




Figure 6A




FIG 7A




FIG 7B




FIG 7C




FIG 7D




FIG 7E




FIG 7F





FIG 7G







FIGURE 8

FIGURE 9






FIGURE 10